



VESPA GTS 300 HPE

GTS 300 HPE



GTS SUPER 300 HPE



GTS SUPER SPORT 300 HPE



GTS SUPER TECH 300 HPE



Engine	Single cylinder 4-stroke, 4 valves, electronic injection, HPE
Displacement	278 cc
Bore x stroke	75 mm x 63 mm
Max Power at the crank shaft	17.5 kW - 23.8 HP - at 8,250 rpm
Max Torque	26 Nm at 5,250 rpm
Consumption	31.2 km/l
CO2 emissions compliance	74 g/km
Fuel system	Electronic injection
Cooling	Liquid
Starter	Electric
Gearbox	CVT continuously variable transmission with torque server
Clutch	Automatic centrifugal dry clutch with vibration dampers
Load-bearing structure	Sheet steel body with welded reinforcements
Front suspension	Single-sided link arm with coil spring and hydraulic shock absorber
Rear suspension	Dual hydraulic shock absorbers with coil spring with preload with 4 position height adjustment
Front brake	Ø 220 mm stainless steel disc with hydraulic control
Rear brake	Ø 220 mm stainless steel disc with hydraulic control
ABS/ASR system	ABS/ASR as standard
Front tyre	Tubeless 120/70 - 12"
Rear tyre	Tubeless 130/70 - 12"
Length/Width/Wheelbase	1,950 mm / 755 mm / 1,375 mm
Seat Height	790 mm
Fuel tank capacity	8.5 Litres
Emissions compliance	Euro 5

AWB
A. N. BOUKATHER

01 888 298