



VESPA PRIMAVERA 150 **IGET ABS**



Engine	3-valve 4-stroke single cylinder i-get catalyzed
Displacement	155 cc
Bore x stroke	58 mm x 58,6 mm
Max Power at the crank shaft	9,2 kW - 12,5 CV - 7,750
Max Torque	12.4 Nm a 6,750 rpm
Consumption	37 km/l
CO2 emissions compliance	63 g/km
Fuel system	Electronic Injection
Cooling	Forced air
Starter	Electric
Gearbox	CVT automatic with torque server
Clutch	Automatic dry centrifugal with shock absorbers
Load-bearing structure	Sheet steel shell with welded structural reinforcements
Front suspension	Single arm with helical spring and hydraulic shock absorber
Rear suspension	Helical spring with adjustable preload (4 positions) and single hydraulic shock absorber
Front brake	Stainless steel Ø 220 mm disc with hydraulic control
Rear brake	Ø 140 mm drum with mechanical control
ABS/ASR system	ABS at the front wheel only
Front tyre	Tubeless 110/70 - 12"
Rear tyre	Tubeless 120/70 - 12"
Length/Width/Wheelbase	1.870 / 735 / 1.340 mm
Seat Height	790 mm
Fuel tank capacity	8 litres
Emissions compliance	Euro 5

ANB
A. N. BOUKATHER

01 888 298